


# NON ROTATE WIRE ROPE

## 19X7 ROTATION RESISTANT

SPECIFICATION: RR-W-410D

EXTRA IMPROVED PLOW STEEL (EIPS)


NOMINAL DIAMETER (MINIMUM)	APPROX WEIGHT	MIN BREAKING STRENGTH	STOCK NUMBER
		UNGALV	
INCH	LBS/FT	LB	19X7
3/16"	0.063	3,140	C75
1/4"	0.115	5,520	J75
5/16"	0.180	8,600	K75
3/8"	0.250	12,300	L75
7/16"	0.350	16,600	M75
1/2"	0.450	21,600	N75
9/16"	0.580	27,200	O75
5/8"	0.710	33,600	A75
3/4"	1.020	48,000	Q75
7/8"	1.390	65,000	R75
1"	1.820	84,400	S75



19 X 7

## DYTY-19 COMPACTED ROTATION RESISTANT

NOMINAL DIAMETER	APPROX WEIGHT	MIN BREAKING STRENGTH	STOCK NUMBER
		TONS	
INCH	LBS/FT	TONS	19X19
1/2"	0.51	14.15	N79
9/16"	0.65	17.90	O79
5/8"	0.81	22.75	A79
3/4"	1.14	32.30	Q79
7/8"	1.56	43.80	R79
1"	2.04	57.20	S79
1 1/8"	2.59	72.60	T79



19 X 19

Wire rope products will break if abused, misused, or Overused. Regular inspection and maintenance are necessary. Consult industry recommendations and applicable codes before using.

7 X 7 X 19

