


DYTY-6, CABLE LAID, SANDLINE WIRE ROPE

DYTY-6 COMPACTED


NOMINAL DIAMETER	APPROX WEIGHT	MIN BREAKING STRENGTH	STOCK NUMBER	
			INCH	LB/FT
3/8"	0.27	8.80	L49	L69
7/16"	0.37	11.90	M49	M69
1/2"	0.48	15.30	N49	N69
9/16"	0.62	19.30	O49	O69
5/8"	0.76	22.70	A49	A69
3/4"	1.09	32.40	Q49	Q69
7/8"	1.49	43.80	R49	R69
1"	1.94	56.90	S49	S69
1 1/8"	2.46	71.50	T49	T69




6 X 26

CABLE LAID WIRE ROPE 7X7X7 & 7X7X19

NOMINAL DIAMETER	APPROX WEIGHT		MIN BREAKING STRENGTH		STOCK NUMBER	
	INCH	LBS/FT	7X7X7	7X7X19	7X7X7	7X7X19
1/4"	0.085	N/A	6,000 LBS	N/A	J10	N/A
3/8"	0.24	N/A	12,560 LBS	N/A	L10	N/A
1/2"	0.359	N/A	21,490 LBS	N/A	N10	N/A
9/16"	0.449	N/A	26,840 LBS	N/A	O10	N/A
5/8"	0.598	N/A	32,180 LBS	N/A	A10	N/A
3/4"	N/A	0.878	N/A	44,000 LBS	N/A	Q10
7/8"	N/A	1.105	N/A	58,400 LBS	N/A	R10
1"	N/A	1.337	N/A	74,290 LBS	N/A	S10
1 1/8"	N/A	2.026	N/A	91,700 LBS	N/A	T10




7 X 7 X 7



6X7 FIBERCORE SANDLINE SPECIFICATION: RR-W-410D

IMPROVED PLOW STEEL (IPS), RRL

ROPE DIAMETER		APPROX WEIGHT	MINIMUM BREAKING STRENGTH	STOCK NUMBER
NOMINAL (MINIMUM)	MAXIMUM			
INCH	INCH	LBS/FT	LBS/1000'	
1/4"	0.265	0.097	5,280	J85
5/16"	0.328	0.151	8,200	K85
3/8"	0.394	0.218	11,270	L85
7/16"	0.459	0.296	15,860	M85
1/2"	0.525	0.387	20,600	N85
9/16"	0.591	0.49	26,000	O85
5/8"	0.656	0.605	31,800	A85
3/4"	0.788	0.87	45,400	Q85



6 X 7 + FC

Wire rope products will break if abused, misused, or Overused. Regular inspection and maintenance are necessary. Consult industry recommendations and applicable codes before using.

