

COATED WIRE ROPE

PVC COATED CABLE

IMPROVED PLOW STEEL (IPS)



7 X 7




7 X 19

DIAMETER		UNIT WEIGHT			BREAKING STRENGTH LBS	STOCK NUMBER
INNER CABLE	OUTER COVER	INNER CABLE LBS/1000'	COATING LBS/1000'	TOTAL LBS/1000'		
7 X 7 PVC						
3/64"	1/16"	4.20	0.84	5.04	270	C1D
1/16"	3/32"	7.50	2.40	9.90	480	D1E
1/16"	1/8"	7.50	5.78	13.28	480	D1F
3/32"	1/8"	16.00	3.40	19.40	920	E1F
3/32"	3/16"	16.00	13.02	29.02	920	E1H
1/8"	3/16"	28.50	9.64	38.14	1,700	F1H
3/16"	1/4"	62.00	13.50	75.50	3,700	H1J
7 X 19 PVC						
1/8"	5/32"	29.00	4.34	33.34	2,000	F2G
1/8"	3/16"	29.00	9.64	38.64	2,000	F2H
5/32"	3/16"	45.00	18.80	63.80	2,800	G2H
3/16"	1/4"	65.00	13.50	78.50	4,200	H2J
1/4"	5/16"	110.00	17.40	127.40	7,000	J2K
5/16"	3/8"	173.00	21.20	194.20	9,800	K2L
5/16"	7/16"	173.00	46.30	219.30	9,800	K2M
3/8"	7/16"	243.00	25.10	268.10	14,400	L2M

6X19 PVC COATED

INSIDE WIRE DIAMETER	WEIGHT	MIN BREAKING STRENGTH	STOCK NUMBER
	LBS/1000 FT		
1/2"	490.00	23,000 LBS	N45P
9/16"	630.00	29,000 LBS	O45P
5/8"	780.00	35,800 LBS	A45P
3/4"	1130.00	51,200 LBS	Q45P
7/8"	1540.00	69,200 LBS	R45P
1"	2000.00	89,800 LBS	S45P



6 X 19

Wire rope products will break if abused, misused, or Overused. Regular inspection and maintenance are necessary. Consult industry recommendations and applicable codes before using

