


GALVANIZED AIRCRAFT CABLE


GALVANIZED CABLE NOT FOR AIRCRAFT USE

NOMINAL DIAMETER	TOLERANCE ON DIAMETER	APPROX WEIGHT	MIN BREAKING STRENGTH	STOCK NUMBER
INCHES	INCHES	LBS/1000'	LBS	
7 X 7				
3/64"	0.008	4.2	270 LBS	C12
1/16"	0.010	7.5	480 LBS	D12
3/32"	0.012	16	920 LBS	E12
1/8"	0.014	28.5	1700 LBS	F12
5/32"	0.016	43	2600 LBS	G12
3/16"	0.018	62	3700 LBS	H12
1/4"	0.018	106	6100 LBS	J12
5/16"	0.022	167	9200 LBS	K12
3/8"	0.026	236	13300LBS	L12
7 X 19				
3/32"	0.012	17.4	1000 LBS	E22
1/8"	0.014	29	2000 LBS	F22
5/32"	0.016	45	2800 LBS	G22
3/16"	0.018	65	4200 LBS	H22
7/32"	0.018	86	5600 LBS	I22
1/4"	0.018	110	7000 LBS	J22
5/16"	0.022	173	9800 LBS	K22
3/8"	0.026	243	14400 LBS	L22
1 X 19				
3/64"	0.008	4.7	280 LBS	C11
1/16"	0.010	8.4	500LBS	D11
3/32"	0.012	18	1200 LBS	E11
1/8"	0.014	33.6	2100 LBS	F11
5/32"	0.016	52.5	3300 LBS	G11
3/16"	0.018	75.4	4700 LBS	H11
1/4"	0.018	134	8200 LBS	J11
5/16"	0.022	210	12500 LBS	K11
3/8"	0.026	302	18000 LBS	L11


7 X 7



7 X 19



1 X 19



REEL LENGTHS AVAILABLE IN 250, 500, 1,000 & 5,000 FEET.

HOW TO ORDER:

EXAMPLE: 1/4" 7X19 X 500 FT REEL, ORDER: J22-0500

Wire rope products will break if abused, misused, or
Overused. Regular inspection and maintenance are necessary.
Consult industry recommendations and applicable codes before using

