

STAINLESS STEEL WIRE ROPE


STAINLESS STEEL CABLE

TYPE 302 – 304 (TYPE 316 AVAILABLE)


NOT FOR AIRCRAFT USE

NOMINAL DIAMETER	TOLERANCE ON DIAMETER	APPROX WEIGHT	MIN BREAKING STRENGTH	STOCK NUMBER
INCHES	INCHES	LBS/1000'	LBS	
7 X 7				
1/32"	0.006	2.5	150 LBS	B13
3/64"	0.008	4.2	270 LBS	C13
1/16"	0.010	7.5	480 LBS	D13
3/32"	0.012	16	920 LBS	E13
1/8"	0.014	28.5	1700 LBS	F13
5/32"	0.016	43	2400 LBS	G13
3/16"	0.018	62	3700 LBS	H13
1/4"	0.018	106	6100 LBS	J13
5/16"	0.022	167	9000 LBS	K13
3/8"	0.026	236	12600 LBS	L13
7 X 19				
1/16"	0.010	7.5	480 LBS	D23
3/32"	0.012	17.4	920 LBS	E23
1/8"	0.014	29	1760 LBS	F23
5/32"	0.016	45	2400 LBS	G23
3/16"	0.018	65	3700 LBS	H23
7/32"	0.018	86	5000 LBS	I23
1/4"	0.018	110	6400 LBS	J23
5/16"	0.022	173	9000 LBS	K23
3/8"	0.026	243	12000 LBS	L23
1 X 19				
3/64"	0.008	4.7	280 LBS	C18
1/16"	0.010	8.4	500 LBS	D18
3/32"	0.012	18	1200 LBS	E18
1/8"	0.014	33.6	2100 LBS	F18
5/32"	0.016	52.5	3300 LBS	G18
3/16"	0.018	75.4	4700 LBS	H18
7/32"	0.018	102	6300 LBS	I18
1/4"	0.018	134	8200 LBS	J18
5/16"	0.022	210	12500 LBS	K18
3/8"	0.026	302	18000 LBS	L18
6X25				
7/16"	N/A	356 LBS	16,300 LBS	M43
1/2"	N/A	458 LBS	22,800 LBS	N43
9/16"	N/A	590 LBS	28,500 LBS	O43
5/8"	N/A	715 LBS	35,000 LBS	A43
3/4"	N/A	922 LBS	49,600 LBS	Q43
7/8"	N/A	1,430 LBS	66,500 LBS	R43
1"	N/A	1,870 LBS	85,400 LBS	S43



7 X 7



7 X 19



1 X 19



6X25

REEL LENGTHS AVAILABLE IN 250, 500, 1,000, 2,500, 3,000, AND 5,000 FEET
HOW TO ORDER: EXAMPLE 1/4" 7X19 X 500' REEL, ORDER: J23-0500

Wire rope products will break if abused, misused, or Overused. Regular inspection and maintenance are necessary. Consult industry recommendations and applicable codes before using

