

CHAIN PROOF COIL G30

PROOF COIL GRADE 30 (INTERNATIONAL)



SIZE	FINISH*	WEIGHT	UNIT	DRUM PKG	WORKING LOAD LIMIT	STOCK NO.
3/16"	EG	0.33 LBS	FT	800'	800 LBS	00-0001
3/16"	HDG	0.40 LBS	FT	800'	800 LBS	00-0011
1/4"	EG	0.63 LBS	FT	400'/800'	1,300 LBS	10-0001
1/4"	SC	0.63 LBS	FT	400'/800'	1,300 LBS	11-0001
1/4"	HDG	0.63 LBS	FT	400'/800'	1,300 LBS	10-0011
5/16"	EG	0.91 LBS	FT	275'/550'	1,900 LBS	20-0001
5/16"	SC	0.91 LBS	FT	275'/550'	1,900 LBS	21-0001
5/16"	HDG	0.91 LBS	FT	275'/550'	1,900 LBS	20-0011
3/8"	EG	1.35 LBS	FT	200'/400'	2,650 LBS	30-0001
3/8"	SC	1.35 LBS	FT	200'/400'	2,650 LBS	31-0001
3/8"	HDG	1.35 LBS	FT	200'/400'	2,650 LBS	30-0011
1/2"	EG	2.42 LBS	FT	100'/200'	4,500 LBS	50-0001
1/2"	SC	2.42 LBS	FT	100'/200'	4,500 LBS	51-0001
1/2"	HDG	2.42 LBS	FT	100'/200'	4,500 LBS	50-0011
5/8"	HDG	3.67 LBS	FT	150'	6,900 LBS	60-0011
3/4"	HDG	5.76 LBS	FT	100'	10,600 LBS	70-0011
1"	HDG	9.49 LBS	FT	60'	17,900 LBS	90-0011

*EG =ELECTRO-GALVANIZED *HDG = HOT DIPPED GALVANIZED *SC =SELF COLORED



550' 800'

PROOF COIL GRADE 30 (DOMESTIC)



275' 400'

SIZE	FINISH*	WEIGHT	UNIT	DRUM PKG	WORKING LOAD LIMIT	STOCK NO.
3/16"	EG	0.21 LBS	FT	800'	800 LBS	00-0051
1/4"	EG	0.69 LBS	FT	400'/800'	1,300 LBS	10-0051
1/4"	SC	0.69 LBS	FT	400'/800'	1,300 LBS	11-0051
5/16"	EG	1.00 LBS	FT	275'/550'	1,900 LBS	20-0051
5/16"	SC	1.00 LBS	FT	275'/550'	1,900 LBS	21-0051
3/8"	EG	1.45 LBS	FT	275'/550'	2,650 LBS	30-0051
3/8"	SC	1.45 LBS	FT	275'/550'	2,650 LBS	31-0051

*EG = ELECTRO-GALVANIZED

*SC = SELF COLORED

PROOF COIL- EG-GRADE 30 (PAILS) (INTERNATIONAL)



500', 250', 141', 92', 63'

SIZE	FINISH*	WEIGHT	UNIT	PAIL QTY	WORKING LOAD LIMIT	STOCK NO.
3/16"	EG	87.50 LBS	PAIL	250'	800 LBS	00-0009
1/4"	EG	90.00 LBS	PAIL	141'	1,300 LBS	10-0009
5/16"	EG	85.00 LBS	PAIL	92'	1,900 LBS	20-0009
3/8"	EG	86.00 LBS	PAIL	63'	2,650 LBS	30-0009
1/2"	EG	50.04 LBS	PAIL	36'	4,500 LBS	50-0009

*EG = ELECTRO-GALVANIZED

*SC = SELF COLORED

WARNING

To prevent the possibility of serious bodily injury:

- DO NOT EXCEED the working load limits for chain or components.
- DO NOT USE for overhead lifting or hoisting.
- DO NOT USE if the chain or components are visibly distorted or worn.